

Fig. 108

Hochdruck-Absperrventil, beiderseits BSPP Innengewinde, Material: 1.0460, 1.4571, 1.4104, 1.7335

A	DN	PN / Bar	C°	L1 / mm	L2 / mm	L3 / mm	F / mm	Material	Art.Nr.
G1/4	5	640	-20°C / +540°	80	115	15	70	1.7335	10108020
G1/4	5	640	-20°C / +250°	80	115	15	70	1.4571	10108023
G1/4	5	640	-20°C / +400°	80	115	15	70	1.4104	10108024
G1/4	5	640	-20°C / +400°	80	115	15	70	1.0460	10108025
G3/8	6	640	-20°C / +540°	80	115	15	70	1.7335	10108030
G3/8	6	640	-20°C / +250°	80	115	15	70	1.4571	10108033
G3/8	6	640	-20°C / +400°	80	115	15	70	1.4104	10108034
G3/8	6	640	-20°C / +400°	80	115	15	70	1.0460	10108035
G1/2	8	640	-20°C / +540°	80	115	17	70	1.7335	10108040
G1/2	8	640	-20°C / +250°	80	115	17	70	1.4571	10108043
G1/2	8	640	-20°C / +400°	80	115	17	70	1.4104	10108044
G1/2	8	640	-20°C / +400°	80	115	17	70	1.0460	10108045
G3/4	10	320	-20°C / +540°	100	135	19	90	1.7335	10108060
G3/4	10	320	-20°C / +250°	100	135	19	90	1.4571	10108063
G3/4	10	320	-20°C / +400°	100	135	19	90	1.4104	10108064
G3/4	10	320	-20°C / +400°	100	135	19	90	1.0460	10108065
G1	15	320	-20°C / +540°	130	165	21	100	1.7335	10108080
G1	15	320	-20°C / +250°	130	165	21	100	1.4571	10108083
G1	15	320	-20°C / +400°	130	165	21	100	1.4104	10108084
G1	15	320	-20°C / +400°	130	165	21	100	1.0460	10108085
G1 1/4	18	160	-20°C / +540°	130	165	22	100	1.7335	10108100



G1 1/4	18	160	-20°C / +250°C	30	165	22	100	1.4571	10108103
G1 1/4	18	160	-20°C / +400°C	30	165	22	100	1.4104	10108104
G1 1/4	18	160	-20°C / +400°C	30	165	22	100	1.0460	10108105
G1 1/2	24	160	-20°C / +540°C	60	220	24	150	1.7335	10108120
G1 1/2	24	160	-20°C / +250°C	60	220	24	150	1.4571	10108123
G1 1/2	24	160	-20°C / +400°C	60	220	24	150	1.0460	10108125

